

Safety Data Sheet dated 8/3/2016, version 3

---

**SECTION 1: Identification of the substance/mixture and of the company/undertaking**

1.1. Product identifier

Mixture identification

Trade name: SOFT POWER CAPS

1.2. Relevant identified uses of the substance or mixture and uses advised against

Recommended use:

Additive for laundry.

Uses advised against:

Do not use in combination with other products.

1.3. Details of the supplier of the safety data sheet

Manufacturer:

SUTTER INDUSTRIES s.p.a. - Società con Unico Socio

15060 Borghetto Borbera (AL) Italia

Tel. +39 0143 631.1

Competent person responsible for the safety data sheet:

regulatory.affairs@sutter.it

1.4. Emergency telephone number

+39 0143 631.1

---

**SECTION 2: Hazards identification**

2.1. Classification of the substance or mixture

EC regulation criteria 1272/2008 (CLP)

Aquatic Chronic 3, Harmful to aquatic life with long lasting effects.

Adverse physicochemical, human health and environmental effects:

No other hazards

2.2. Label elements

Hazard pictograms:

None

Hazard statements:

H412 Harmful to aquatic life with long lasting effects.

Precautionary statements:

None

Special Provisions:

EUH210 Only for professional use. Safety data sheet available on request.

Contents

METHYLCHLOROISOTHIAZOLINONE, METHYLISOTHIAZOLINONE: May produce an allergic reaction.

Product contents:

cationic surfactants 5 - 15 %

non-ionic surfactants < 5 %

The product also contains: Perfumes, Optical bleaches

Allergens: EUGENOL, BUTYLPHENYL METHYLPROPIONAL, HEXYL CINNAMAL, COUMARIN, LINALOOL, CITRONELLOL

Preservatives: METHYLCHLOROISOTHIAZOLINONE, METHYLISOTHIAZOLINONE

Special provisions according to Annex XVII of REACH and subsequent amendments:

## Safety Data Sheet

### SOFT POWER CAPS

- None
- 2.3. Other hazards  
vPvB Substances: None - PBT Substances: None
- Other Hazards:  
No other hazards

---

#### SECTION 3: Composition/information on ingredients

##### 3.1. Substances


N.A.

##### 3.2. Mixtures

Hazardous components within the meaning of the CLP regulation and related classification:

>= 1% - < 3% PROPAN-2-OL

REACH No.: 01-2119457558-25, Index number: 603-117-00-0, CAS: 67-63-0, EC: 200-661-7


 2.6/2 Flam. Liq. 2 H225

 3.3/2 Eye Irrit. 2 H319

 3.8/3 STOT SE 3 H336


>= 0.25% - < 0.5% SCENTED ESSENCES R50/53 M=1

 4.1/A1 Aquatic Acute 1 H400 M=1.

 4.1/C1 Aquatic Chronic 1 H410 M=1.

>= 0.01% - < 0.1% 4-TERT-BUTYLCYCLOHEXYLACETATE

REACH No.: 01-2119976286-24, CAS: 32210-23-4, EC: 250-954-9

 4.1/C2 Aquatic Chronic 2 H411

 3.4.2/1 Skin Sens. 1 H317

---

#### SECTION 4: First aid measures

##### 4.1. Description of first aid measures

In case of skin contact:

Wash with plenty of water and soap.

In case of eyes contact:

In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.

In case of Ingestion:

Do not under any circumstances induce vomiting. OBTAIN A MEDICAL EXAMINATION IMMEDIATELY.

In case of Inhalation:

Remove casualty to fresh air and keep warm and at rest.

##### 4.2. Most important symptoms and effects, both acute and delayed

None

##### 4.3. Indication of any immediate medical attention and special treatment needed

Treatment:

None

---

#### SECTION 5: Firefighting measures

##### 5.1. Extinguishing media

Suitable extinguishing media:

## Safety Data Sheet

### SOFT POWER CAPS

Water.

Carbon dioxide (CO<sub>2</sub>).

Extinguishing media which must not be used for safety reasons:

None in particular.

5.2. Special hazards arising from the substance or mixture

Do not inhale explosion and combustion gases.

Burning produces heavy smoke.

5.3. Advice for firefighters

Use suitable breathing apparatus .

Collect contaminated fire extinguishing water separately. This must not be discharged into drains.

Move undamaged containers from immediate hazard area if it can be done safely.

---

### SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Wear personal protection equipment.

Remove all sources of ignition.

Remove persons to safety.

See protective measures under point 7 and 8.

6.2. Environmental precautions

Do not allow to enter into soil/subsoil. Do not allow to enter into surface water or drains.

Retain contaminated washing water and dispose it.

In case of gas escape or of entry into waterways, soil or drains, inform the responsible authorities.

Suitable material for taking up: absorbing material, organic, sand

6.3. Methods and material for containment and cleaning up

Wash with plenty of water.

6.4. Reference to other sections

See also section 8 and 13

---

### SECTION 7: Handling and storage

7.1. Precautions for safe handling

Avoid contact with skin and eyes, inhalation of vapours and mists.

Don't use empty container before they have been cleaned.

Before making transfer operations, assure that there aren't any incompatible material residuals in the containers.

Contaminated clothing should be changed before entering eating areas.

Do not eat or drink while working.

See also section 8 for recommended protective equipment.

7.2. Conditions for safe storage, including any incompatibilities

Store away from sunlight.

Store in a cool and well ventilated place.

Keep away from food, drink and feed.

Incompatible materials:

None in particular.

Instructions as regards storage premises:

Adequately ventilated premises.

7.3. Specific end use(s)

None in particular

---

### SECTION 8: Exposure controls/personal protection

8.1. Control parameters

PROPAN-2-OL - CAS: 67-63-0

**Safety Data Sheet**  
**SOFT POWER CAPS**

ACGIH - LTE(8h): 492 mg/m<sup>3</sup>, 200 ppm - STE: 983 mg/m<sup>3</sup>, 400 ppm - Notes: A4, BEI  
- Eye and URT irr, CNS impair

4-TERT-BUTYLCYCLOHEXYLACETATE - CAS: 32210-23-4

ACGIH - LTE(8h): 713 mg/m<sup>3</sup> - STE(15min): 950 mg/m<sup>3</sup> - Notes: TLV

**DNEL Exposure Limit Values**

PROPAN-2-OL - CAS: 67-63-0

Worker Industry: 888 mg/kg - Consumer: 319 mg/kg - Exposure: Human Dermal -  
Frequency: Long Term, systemic effects

Worker Industry: 500 mg/m<sup>3</sup> - Consumer: 89 mg/m<sup>3</sup> - Exposure: Human Inhalation -  
Frequency: Long Term, systemic effects

Consumer: 26 mg/kg - Exposure: Human Oral - Frequency: Long Term, systemic  
effects

**PNEC Exposure Limit Values**

PROPAN-2-OL - CAS: 67-63-0

Target: Microorganisms in sewage treatments - Value: 2251 mg/l

Target: Marine water sediments - Value: 552 mg/kg

Target: Soil (agricultural) - Value: 28 mg/kg

Target: Marine water - Value: 140.9 mg/l

**8.2. Exposure controls**

**Eye protection:**

Not needed for normal use. Anyway, operate according good working practices.

**Protection for skin:**

No special precaution must be adopted for normal use.

**Protection for hands:**

Not needed for normal use.

**Respiratory protection:**

Not needed for normal use.

**Thermal Hazards:**

None

**Environmental exposure controls:**

None

**Appropriate engineering controls:**

None

**SECTION 9: Physical and chemical properties**

**9.1. Information on basic physical and chemical properties**

Properties	Value	Method:	Notes:
Appearance and colour:	Opaque liquid, blue	--	--
Odour:	Floral	--	--
Odour threshold:	Evident	--	--
pH:	2,7 +/- 0,5	--	--
Melting point / freezing point:	N.A.	--	--
Initial boiling point and boiling range:	>= 100 °C	--	--
Flash point:	> 65 °C	--	--
Evaporation rate:	N.A.	--	--
Solid/gas flammability:	N.A.	--	--
Upper/lower flammability or explosive limits:	N.A.	--	--

## Safety Data Sheet

### SOFT POWER CAPS

Vapour pressure:	N.A.	--	--
Vapour density:	N.A.	--	--
Relative density:	1,003 g/ml	--	--
Solubility in water:	Total	--	--
Solubility in oil:	Partial	--	--
Partition coefficient (n-octanol/water):	< 1000	--	--
Auto-ignition temperature:	N.A.	--	--
Decomposition temperature:	N.A.	--	--
Viscosity:	150 +/- 50 cP	--	--
Explosive properties:	N.A.	--	--
Oxidizing properties:	N.A.	--	--

#### 9.2. Other information

Properties	Value	Method:	Notes:
Miscibility:	N.A.	--	--
Fat Solubility:	N.A.	--	--
Conductivity:	N.A.	--	--
Substance Groups relevant properties	Not Relevant	--	--

## SECTION 10: Stability and reactivity

- 10.1. Reactivity
  - Stable under normal conditions
- 10.2. Chemical stability
  - Stable under normal conditions
- 10.3. Possibility of hazardous reactions
  - None
- 10.4. Conditions to avoid
  - Stable under normal conditions.
- 10.5. Incompatible materials
  - None in particular.
- 10.6. Hazardous decomposition products
  - None.

## SECTION 11: Toxicological information

### 11.1. Information on toxicological effects

Toxicological information of the mixture:

N.A.

Toxicological information of the main substances found in the mixture:

PROPAN-2-OL - CAS: 67-63-0

a) acute toxicity:

Test: LD50 - Route: Oral - Species: Rat > 5000 mg/kg

Test: LC50 - Route: Inhalation - Species: Rat > 10000 ppm - Duration: 6h

Test: LD50 - Route: Skin - Species: Rabbit > 5000 mg/kg

Test: LD50 - Route: Skin - Species: Rat = 12800 mg/kg

4-TERT-BUTYLCYCLOHEXYLACETATE - CAS: 32210-23-4

a) acute toxicity:

Test: LD50 - Route: Oral - Species: Rabbit = 3200 mg/kg

Test: LD50 - Route: Skin - Species: Rabbit > 17600 mg/kg

Test: LC50 - Route: Inhalation - Species: Rat = 390 ppm - Duration: 4h

If not differently specified, the information required in Regulation (EU)2015/830 listed below must be considered as N.A.:

- a) acute toxicity;
- b) skin corrosion/irritation;
- c) serious eye damage/irritation;
- d) respiratory or skin sensitisation;
- e) germ cell mutagenicity;
- f) carcinogenicity;
- g) reproductive toxicity;
- h) STOT-single exposure;
- i) STOT-repeated exposure;
- j) aspiration hazard.

---

## **SECTION 12: Ecological information**

### 12.1. Toxicity

Adopt good working practices, so that the product is not released into the environment.

PROPAN-2-OL - CAS: 67-63-0

a) Aquatic acute toxicity:

Endpoint: LC50 - Species: Fish > 100 mg/l - Duration h: 48 - Notes: Leuciscus idus

Endpoint: EC50 - Species: Daphnia > 100 mg/l - Duration h: 24 - Notes: Daphnia magna

Endpoint: EC50 - Species: Algae > 100 mg/l - Duration h: 72 - Notes: Scenedesmus quadricauda

SCENTED ESSENCES R50/53 M=1

a) Aquatic acute toxicity:

Endpoint: LC50 = 0.11 mg/l

4-TERT-BUTYLCYCLOHEXYLACETATE - CAS: 32210-23-4

a) Aquatic acute toxicity:

Endpoint: LC50 - Species: Fish = 17 mg/l - Duration h: 96 - Notes: Pimephales promelas

Endpoint: EC50 - Species: Daphnia = 73 mg/l - Duration h: 24 - Notes: Daphnia magna

Endpoint: EC50 - Species: Algae = 320 mg/l - Duration h: 96 - Notes: Scenedesmus subspicatus

### 12.2. Persistence and degradability

None

N.A.

### 12.3. Bioaccumulative potential

N.A.

### 12.4. Mobility in soil

N.A.

### 12.5. Results of PBT and vPvB assessment

vPvB Substances: None - PBT Substances: None

### 12.6. Other adverse effects

None

---

## **SECTION 13: Disposal considerations**

### 13.1. Waste treatment methods

Recover if possible. In so doing, comply with the local and national regulations currently in force.

---

## **SECTION 14: Transport information**

## Safety Data Sheet

### SOFT POWER CAPS

- 14.1. UN number  
Not classified as dangerous in the meaning of transport regulations.
- 14.2. UN proper shipping name  
N.A.
- 14.3. Transport hazard class(es)  
N.A.
- 14.4. Packing group  
N.A.
- 14.5. Environmental hazards  
ADR-Environmental Pollutant: No  
IMDG-Marine pollutant: No
- 14.6. Special precautions for user  
N.A.
- 14.7. Transport in bulk according to Annex II of Marpol and the IBC Code  
N.A.

---

#### SECTION 15: Regulatory information

- 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture  
Dir. 98/24/EC (Risks related to chemical agents at work)  
Dir. 2000/39/EC (Occupational exposure limit values)  
Regulation (EC) n. 1907/2006 (REACH)  
Regulation (EC) n. 1272/2008 (CLP)  
Regulation (EC) n. 790/2009 (ATP 1 CLP) and (EU) n. 758/2013  
Regulation (EU) 2015/830  
Regulation (EU) n. 286/2011 (ATP 2 CLP)  
Regulation (EU) n. 618/2012 (ATP 3 CLP)  
Regulation (EU) n. 487/2013 (ATP 4 CLP)  
Regulation (EU) n. 944/2013 (ATP 5 CLP)  
Regulation (EU) n. 605/2014 (ATP 6 CLP)
- Restrictions related to the product or the substances contained according to Annex XVII Regulation (EC) 1907/2006 (REACH) and subsequent modifications:  
None
- Where applicable, refer to the following regulatory provisions :  
Directive 2003/105/CE ('Activities linked to risks of serious accidents') and subsequent amendments.  
Regulation (EC) nr 648/2004 (detergents).  
1999/13/EC (VOC directive)
- Provisions related to directive EU 2012/18 (Seveso III):  
Seveso III category according to Annex 1, part 1  
None
- 15.2. Chemical safety assessment  
No

---

#### SECTION 16: Other information

- Full text of phrases referred to in Section 3:  
H225 Highly flammable liquid and vapour.  
H319 Causes serious eye irritation.  
H336 May cause drowsiness or dizziness.  
H400 Very toxic to aquatic life.  
H410 Very toxic to aquatic life with long lasting effects.



## Safety Data Sheet

### SOFT POWER CAPS

H411 Toxic to aquatic life with long lasting effects.  
H317 May cause an allergic skin reaction.  
H314 Causes severe skin burns and eye damage.  
H301 Toxic if swallowed.  
H311 Toxic in contact with skin.  
H330 Fatal if inhaled.

Paragraphs modified from the previous revision:

SECTION 1: Identification of the substance/mixture and of the company/undertaking  
SECTION 2: Hazards identification  
SECTION 3: Composition/information on ingredients  
SECTION 6: Accidental release measures  
SECTION 8: Exposure controls/personal protection  
SECTION 9: Physical and chemical properties  
SECTION 11: Toxicological information  
SECTION 12: Ecological information  
SECTION 14: Transport information  
SECTION 15: Regulatory information

This document was prepared by a competent person who has received appropriate training.

Main bibliographic sources:

ECDIN - Environmental Chemicals Data and Information Network - Joint Research Centre,  
Commission of the European Communities  
SAX's DANGEROUS PROPERTIES OF INDUSTRIAL MATERIALS - Eight Edition - Van  
Nostrand Reinold

The information contained herein is based on our state of knowledge at the above-specified date. It refers solely to the product indicated and constitutes no guarantee of particular quality.

It is the duty of the user to ensure that this information is appropriate and complete with respect to the specific use intended.

This MSDS cancels and replaces any preceding release.

ADR: European Agreement concerning the International Carriage of Dangerous Goods by Road.  
CAS: Chemical Abstracts Service (division of the American Chemical Society).  
CLP: Classification, Labeling, Packaging.  
DNEL: Derived No Effect Level.  
EINECS: European Inventory of Existing Commercial Chemical Substances.  
GefStoffVO: Ordinance on Hazardous Substances, Germany.  
GHS: Globally Harmonized System of Classification and Labeling of Chemicals.  
IATA: International Air Transport Association.  
IATA-DGR: Dangerous Goods Regulation by the "International Air Transport Association" (IATA).  
ICAO: International Civil Aviation Organization.  
ICAO-TI: Technical Instructions by the "International Civil Aviation Organization" (ICAO).  
IMDG: International Maritime Code for Dangerous Goods.  
INCI: International Nomenclature of Cosmetic Ingredients.  
KSt: Explosion coefficient.  
LC50: Lethal concentration, for 50 percent of test population.  
LD50: Lethal dose, for 50 percent of test population.  
LTE: Long-term exposure.  
PNEC: Predicted No Effect Concentration.  
RID: Regulation Concerning the International Transport of Dangerous Goods



**Safety Data Sheet**  
**SOFT POWER CAPS**

by Rail.  
STE: Short-term exposure.  
STEL: Short Term Exposure limit.  
STOT: Specific Target Organ Toxicity.  
TLV: Threshold Limiting Value.  
TWATLV: Threshold Limit Value for the Time Weighted Average 8 hour day.  
(ACGIH Standard).  
WGK: German Water Hazard Class.